

Nylon Cable Clamps

- Made from nylon for maximum strength.
- Resistant to solvents, oils, acids and moisture.
- Has unique screw hole alignment feature to speed installation.
- Available in natural or UV resistant black for outdoor use.



ABYC Recommends

“Conductors shall be supported throughout their length or, alternatively, shall be secured at least every 18 inches by one of the following methods:

1. Non-metallic clamps of a size to hold the conductors firmly in place. The material shall be resistant to oil, gasoline, and water and shall not break or crack within a temperature range of -30° F to 250° F.
2. Metal straps or clamps with smooth, rounded edges.
3. Metal clamps lined with an insulating material resistant to the effects of oil, gasoline and water.” E8.15.11 and E9.17.10.

Nominal Diameter (in.)	Color	Qty/ Pkg	Item Number
1/8 3.2 mm	Natural	7	401121
		25	401122
		100	401125
	UV Black	7	402121
		25	402122
		100	402125
3/16 4.8 mm	Natural	7	401181
		25	401182
		100	401185
	UV Black	7	402181
		25	402182
		100	402185
1/4 6.4 mm	Natural	6	401251
		25	401252
		100	401255
	UV Black	6	402251
		25	402252
		100	402255
5/16 7.9 mm	Natural	6	401311
		25	401312
		100	401315
	UV Black	6	402311
		25	402312
		100	402315
3/8 9.5 mm	Natural	6	401371
		25	401372
		100	401375
	UV Black	6	402371
		25	402372
		100	402375
1/2 12.7 mm	Natural	5	401501
		25	401502
		100	401505
	UV Black	5	402501
		25	402502
		100	402505
7/16 11.1 mm	Natural	6	401431
		25	401432
		100	401435
	UV Black	5	402431
		25	402432
		100	402435
5/8 15.9 mm	Natural	3	401621
		25	401622
		100	401625
	UV Black	3	402621
		25	402622
		100	402625
3/4 19 mm	Natural	3	401751
		25	401752
		100	401755
	UV Black	3	402751
		25	402752
		100	402755

Nominal Diameter (in.)	Color	Qty/ Pkg	Item Number
7/8 22.2 mm	Natural	3	401871
		25	401872
		100	401875
	UV Black	3	402871
		25	402872
		100	402875
1 25.4 mm	Natural	3	401891
		25	401892
		100	401895
	UV Black	3	402891
		25	402892
		100	402895
1-1/4 32 mm	Natural	2	401911
		25	401912
		100	401915
	UV Black	2	402911
		25	402912
		100	402915
1-1/2 38 mm	Natural	2	401931
		25	401932
		100	401935
	UV Black	2	402931
		25	402932
		100	402935

