

cable ties, clamps & mounts

Flexible Grommeting

- Natural serrated polyethylene.
- Ideal for flat edge applications or small radius holes, this material can be cut to length to provide abrasion resistance.



Panel Width(in)	Feet/Pkg	Cm/Pkg	Item Number
1/16	3	7.6	761062
1.6 mm	100	254	751062
1/8	3	7.6	762125
3.2 mm	100	254	751125
3/16	3	7.6	762187
4.8 mm	100	254	751187
1/4	3	7.6	762250
6.4 mm	100	254	751250

Liquid Tight Wire Seals

- Made of Nylon 6/6 flame resistant, self extinguishing Buna-N form seal.
- Resistant to salt water, acids, alkalis, alcohol, oils.
- Non-corrosive for use in the marine environment.
- All seals exceed NEMA 4 x or 6 specs.
- Provide low cost watertight cable entries into panels and junction boxes.
- UL and CSA listed.
- Good underwater to 300 feet /91.4 m (150 PSIG).

Description	Recommended AWG Range	Thread	Cable Diameter	Clear Hole	Body Length	Thread Length	Qty/Pkg	Item Number
Round Cable	18 - 10 AWG	3/8" NPT	.08"-.24"	.68"	.87"	.59"	1	764998
	.8 - 5 mm							
	10 - 2 AWG	1/2" NPT	.24"-.47"	.83"	1.06"	.51"	1	765000
	5 mm - 32 mm							
	4 - 1/0 AWG	1/2" NPT	.39"-.56"	.83"	1.10"	.51"	1	765002
19 mm - 50 mm								
1 - 3/0 AWG	3/4" NPT	.51"-.71"	1.05"	1.18"	.51"	1	765004	
40 mm - 81 mm								
4/0 AWG	1" NPT	.71"-.98"	1.35"	1.50"	.75"	1	765006	
103 mm								



Description	Recommended AWG Range	Thread	Qty/Pkg	Item Number
Flat Cable	14/3 - 12/3 AWG	1/2" NPT	1	765010
	3 x 2 mm - 3 x 3 mm			
	14/2 - 10/2 AWG			
	2 x 2 mm - 2 x 5 mm			
14/3 - 12/3 AWG	3/4" NPT	1	765012	
3 x 2 mm - 3 x 3 mm				
12/2 - 10/2 AWG				
2 x 3 mm - 2 x 5 mm				



Installation: Push cable through installed strain relief fitting and tighten dome-nut.