

circuit breakers, switches & accessories

Sealed Rocker Switch

(Black Actuator. will fit max. 1/4" panel thickness)

Description	Function	Qty/ Pkg	Item Number
Single Pole Single Throw	on-off	1	554010
	(on)-off	1	554022
Single Pole Double Throw	on-off-on	1	554026
	(on)-off-(on)	1	554028
Double Pole Single Throw	on-off	1	554030
	on-on	1	554038
Double Pole Double Throw	on-off-on	1	554033
	(on)-off-(on)	1	554035

(on) = Momentary

Rating:

20 AMP at 12V (not UL approved).



10 AMP at 250 VAC (UL & CSA approved).

15 AMP at 125 VAC (UL & CSA approved).

Maximum panel thickness 1/4".

Certified for prolonged submersion under pressure (front panel sealing) and is UL Ignition Protected.

Features an easy-to-change actuator (rocker) to allow changes in the actuator color or style.



Single Switch Cut-Out

Sealed Rocker Switch w/Light

(Black Actuator, Red in On position)

Description	Function	Qty/ Pkg	Item Number
Single Pole Single Throw	on-off	1	554024
	(on)-off	1	554011
Single Pole Double Throw	(on)-off-on	1	554012
	on-off-on	1	554027
	(on)-off-(on)	1	554029
Double Pole Single Throw	on-off	1	554032
Double Pole Double Throw	on-off-on	1	554036
	(on)-off-(on)	1	554016

(on) = Momentary

Red Lens, Clear Lamp

