

heat shrink products

Adhesive Lined Heavy Wall Battery Cable Tubing (BCT)



BCT Dia.	BCT Color	Length (inch)	Length (cm)	Qty/Pkg	Item Number				
3/4" 19 mm	Black	3	7.6	3	326103				
		6	15.2	3	326106				
		12	30.5	3	326124				
		48	122	1	326148				
	Black/Red	3	7.6	1/1	326202				
		Red	3	7.6	3	326603			
			6	15.2	3	326606			
			12	30.5	3	326624			
	48	Red	48	122	1	326648			
			1"	Black	3	7.6	3	327103	
					25.4 mm	6	15.2	2	327106
						12	30.5	2	327124
48	122	1				327148			
Black/Red	3	7.6	1/1	327202					
	Red	3	7.6	3	327603				
		6	15.2	2	327606				
		12	30.5	2	327624				
48	Red	48	122	1	327648				
		1 - 1/2"	Black	48	122	1	328148		
				38 mm	Red	48	122	1	328648

Battery Cable Tubing Specifications (3:1 ratio)

Size	Shrinks to	Wire Range (AWG)
3/4"	1/4"	8 - 2/0
19 mm	6.4 mm	8-62 mm ²
1"	3/8"	2 - 4/0
25.4 mm	9.5 mm	32-103 mm ²
1 - 1/2"	1/2"	4/0 - 500 MCM
38 mm	12.7 mm	103-253 mm ²

- **ANCOR** heat shrink connectors offer adhesive built into the sleeve of the heat shrink tubing
- Shrinks to form a water tight seal and the ultimate vibration and strain relief.
- Tinned for corrosion resistance.
- Pure copper for maximum current flow.
- Brazed seam for maximum strength.
- Nylon insulator, preferred by experts, for Marine Grade™ resistance to sunlight, water, oil, chemicals, vibration and cut-through damage.



Adhesive Lined Heat Shrink Butt Connectors

Wire Range	Qty/Pkg	Item Number
22 - 18 0.3-0.8 mm ²	3	309003
	25	309025
	100	309099
	500	309002
16 - 14 1-2 mm ²	3	309103
	25	309125
	100	309199
	500	309102
12 - 10 3-5 mm ²	3	309203
	25	309225
	100	309299
	500	309202



Also available in bulk quantities