

lugs and battery terminals




- Manufactured from heavy duty annealed tinned copper, providing for maximum current flow.
- 100% tin plated copper resists corrosion from salt and moisture.
- Seamless barrel design allows for maximum strength when crimped.
- Closed end design seals out moisture so cables stay dry and corrosion free.

Heavy Duty Lugs

| Cable Range | Screw Size (in) | Screw Size (mm) | Qty/Pkg | Item Number |
|-------------------------|-----------------|-----------------|---------|-------------|
| 8 8 mm ² | 10 | 4.8 | 2 | 252233 |
| | | | 25 | 242233 |
| | | | 100 | 244233 |
| | 1/4 | 6.4 | 2 | 252234 |
| | | | 25 | 242234 |
| | | | 100 | 244234 |
| | 5/16 | 7.9 | 2 | 252235 |
| | | | 25 | 242235 |
| | | | 100 | 244235 |
| | 3/8 | 9.5 | 2 | 252236 |
| | | | 25 | 242236 |
| | | | 100 | 244236 |
| 1/2 | 12.7 | 2 | 252237 | |
| | | 10 | 242237 | |
| | | 100 | 244237 | |
| 5/16 & 3/8 | 7.9 & 9.5 | 1/1 | 252231 | |
| | | | | |
| | | | | |
| 6 13 mm ² | 10 | 4.8 | 2 | 252243 |
| | | | 25 | 242243 |
| | | | 100 | 244243 |
| | 1/4 | 6.4 | 2 | 252244 |
| | | | 25 | 242244 |
| | | | 100 | 244244 |
| | 5/16 | 7.9 | 2 | 252245 |
| | | | 25 | 242245 |
| | | | 100 | 244245 |
| | 3/8 | 9.5 | 2 | 252246 |
| | | | 25 | 242246 |
| | | | 100 | 244246 |
| 1/2 | 12.7 | 2 | 252247 | |
| | | 10 | 242247 | |
| | | 100 | 244247 | |
| 5/16 & 3/8 | 7.9 & 9.5 | 1/1 | 252241 | |
| | | | | |
| | | | | |
| 4 21 mm ² | 10 | 4.8 | 2 | 252253 |
| | | | 25 | 242253 |
| | | | 100 | 244253 |
| | 1/4 | 6.4 | 2 | 252254 |
| | | | 25 | 242254 |
| | | | 100 | 244254 |

| Cable Range | Screw Size (in) | Screw Size (mm) | Qty/Pkg | Item Number |
|-------------------------|-----------------|-----------------|---------|-------------|
| 4 21 mm ² | 5/16 | 7.9 | 2 | 252255 |
| | | | 25 | 242255 |
| | | | 100 | 244255 |
| | 3/8 | 9.5 | 2 | 252256 |
| | | | 25 | 242256 |
| | | | 100 | 244256 |
| 1/2 | 12.7 | 2 | 252257 | |
| | | 10 | 242257 | |
| | | 100 | 244257 | |
| 5/16 & 3/8 | 7.9 & 9.5 | 1/1 | 252251 | |
| | | | | |
| | | | | |
| 2 34 mm ² | 1/4 | 6.4 | 2 | 252264 |
| | | | 25 | 242264 |
| | | | 100 | 244264 |
| | 5/16 | 7.9 | 2 | 252265 |
| | | | 25 | 242265 |
| | | | 100 | 244265 |
| 3/8 | 9.5 | 2 | 252266 | |
| | | 25 | 242266 | |
| | | 100 | 244266 | |
| 1/2 | 12.7 | 2 | 252267 | |
| | | 10 | 242267 | |
| | | 100 | 244267 | |
| 5/16 & 3/8 | 7.9 & 9.5 | 1/1 | 252261 | |
| | | | | |
| | | | | |
| 1 42 mm ² | 1/4 | 6.4 | 2 | 252274 |
| | | | 25 | 242274 |
| | | | 100 | 244274 |
| | 5/16 | 7.9 | 2 | 252275 |
| | | | 25 | 242275 |
| | | | 100 | 244275 |
| 3/8 | 9.5 | 2 | 252276 | |
| | | 25 | 242276 | |
| | | 100 | 244276 | |
| 1/2 | 12.7 | 2 | 252277 | |
| | | 10 | 242277 | |
| | | 100 | 244277 | |
| 5/16 & 3/8 | 7.9 & 9.5 | 1/1 | 252271 | |
| | | | | |
| | | | | |

100% Tinned Copper



ABYC Recommends

"Solder shall not be the sole means of mechanical connection in any circuit. Exception: Battery lugs with a solder contact length of not less than 1.5 times the diameter of the conductor." ABYC E-9.16.11.9