

## 1 - 4/0 AWG Battery Cable

UL 1426 Tinned Boat Cable

Cable Size	Color	Spool Length(ft)	Item Number
1 42 mm <sup>2</sup>	Black	25	115002
		50	115005
		100	115010
		300	115030
	Red	25	115502
		50	115505
		100	115510
		300	115530
	Yellow	25	115902
		50	115905
		100	115910
		300	115930
1/0 53 mm <sup>2</sup>	Black	25	116002
		50	116005
		100	116010
		250	116025
	Red	25	116502
		50	116505
		100	116510
		250	116525
	Yellow	25	116902
		50	116905
		100	116910
		250	116925
2/0 68 mm <sup>2</sup>	Black	25	117002
		50	117005
		100	117010
		200	117020

Cable Size	Color	Spool Length(ft)	Item Number
2/0 68 mm <sup>2</sup>	Red	25	117502
		50	117505
		100	117510
		200	117520
	Yellow	25	117902
		50	117905
		100	117910
		200	117920
3/0 85 mm <sup>2</sup>	Black	25	118002
		50	118005
		100	118010
		150	118015
	Red	25	118502
		50	118505
		100	118510
		150	118515
	Yellow	25	118902
		50	118905
		100	118910
		150	118915
4/0 107 mm <sup>2</sup>	Black	25	119002
		50	119005
		100	119010
		100	119010
	Red	25	119502
		50	119505
		100	119510
		100	119510
	Yellow	25	119902
		50	119905
		100	119910
		100	119910



Item #702065 Battery Cable Stripper

- Adjustable blade cutting height, comes with extra blades.
- Easily adjusts to various cable thickness. Swivel blade for stripping up wire as well as around.
- Good for stripping duplex and triplex.
- Comes with extra swivel blade.

made in 

### Marine Grade™ 8 - 4/0 AWG Cable Specifications

Wire Size	Nominal O.D.	Wt. per 1000'	Stranding No. of 30 AWG	Cir. Mil Area	Square mm	Ohms per 1000'
8 AWG 8 mm <sup>2</sup>	5/16" 7.9 mm	86 lbs. 39 kg	168	16,800	8.37	0.62
6 AWG 8 mm <sup>2</sup>	11/32" 8.7 mm	118 lbs. 53.5 kg	266	26,600	13.3	0.04
4 21 mm <sup>2</sup>	13/32" 10.3 mm	178 lbs. 81 kg	420	42,000	21.15	0.24
2 34 mm <sup>2</sup>	15/32" 11.9 mm	277 lbs. 126 kg	665	66,500	33.62	0.157
1 42 mm <sup>2</sup>	17/32" 13.5 mm	350 lbs. 159 kg	836	83,690	44.21	0.127
1/0 53 mm <sup>2</sup>	9/16" 14.3 mm	437 lbs. 198 kg	1064	105,600	53.49	0.099
2/0 68 mm <sup>2</sup>	5/8" 15.9 mm	549 lbs. 249 kg	1330	133,000	67.43	0.077
3/0 85 mm <sup>2</sup>	11/16" 17.5 mm	675 lbs. 306 kg	1665	167,800	85.01	0.062
4/0 107 mm <sup>2</sup>	13/16" 20.6 mm	837 lbs. 380 kg	2109	211,600	107.2	0.049