

Coaxial Cable Assemblies

Premium Tinned Copper

All assemblies come with **ANCOR** Adhesive Lined Heat Shrink to seal out moisture, provide strain relief and fight corrosion.

96% Tinned copper braid for optimum protection against signal loss.

One end pre-assembled coaxial cable packages for RG58 and RG8X come with **ANCOR's** twist-on UHF plugs for easy installation.

No solder or special tools required.

Special low loss SAT NAV extensions.



| Wire Size | Ends Description | Cable Length(ft) | Item Number |
|-----------|--------------------|------------------|-------------|
| RG58CU | Two ends assembled | 3 | 189800 |
| | Two ends assembled | 12 | 189802 |
| RG59U | Two ends assembled | 2 | 189902 |
| RG8X | One end assembled | 35 | 189834 |
| | Two ends assembled | 35 | 189835 |
| | Two ends assembled | 50 | 189850 |
| | One end assembled | 50 | 189849 |
| RG8U | Two ends assembled | 2 | 189870 |
| | One end assembled | 75 | 189874 |

made in USA

Standard Battery Cable Assemblies

UL 1426 Tinned Boat Cable

ANCOR Marine Grade™ Standard Battery Cable Assemblies are manufactured with **ANCOR's** premium UL1426 tinned copper battery cable. The battery cable is fine stranded to produce maximum conductivity and flexibility. In addition, all **ANCOR** battery cable is flame retarded, UV inhibited, rated to 600V and 105°C.

The lugs are tinned copper to avoid corrosion and last longer. Each end has a piece of **ANCOR's** adhesive lined 3:1 heatshrink tubing placed over the electrical connection. The heatshrink tubing seals out moisture and other corrosive elements found in the marine environment. This ensures a longer lasting battery connection.

made in USA



| Cable Size | Color | Length (In) | Stud Size(In) | Item Number |
|-----------------------------|-------|-------------|---------------|-------------|
| 4 AWG 21 mm ² | Black | 18 | 5/16 | 189130 |
| | | 32 | 5/16 | 189134 |
| | | 48 | 5/16 | 189136 |
| | Red | 18 | 3/8 | 189131 |
| | | 32 | 3/8 | 189135 |
| | | 48 | 3/8 | 189137 |
| 2 AWG 34 mm ² | Black | 18 | 5/16 | 189140 |
| | | 32 | 5/16 | 189144 |
| | | 48 | 5/16 | 189146 |
| | Red | 18 | 3/8 | 189141 |
| | | 32 | 3/8 | 189145 |
| | | 48 | 3/8 | 189147 |

Marine Grade™ Battery Cable Assemblies
For Continuous Current Use Battery
Draws up to:
 136 Amps
 178 Amps

Cable Assemblies
 4 AWG
 2 AWG